

[Sense + Act]



Localization [on-site and in transit]



Temperature + Humidity [on-site and in transit]



Shock [on-site and in transit]



Light-detection [on-site or in transit]



Product or man-down [on-site or in transit]



Alarm [on-site or in transit]



Wifi + BLE beacon [on-site or in transit]



[Meet Pharox Diamond Lady]







[Specs]

2 1 3

OLLAND

0

-7

00

0

14

15

23

	Localization	BLE localization, WiFi for location accuracies up to 10 meters, LWPWAN for location accuracies up to 50 meters (if geolocation is installed by local providers). GPS 1-5 m accurate
OR CR	Wi-Fi	Wi-Fi (802.11 B/G/N 2.4Ghz) is included for localization support. WiFi functions can be activated over-the-air
I C C C C C C C C C C C C C C C C C C C	Bluetooth BLE	BLE for BT beaconing and device management/read-out
The The	Temperature	Precise temperature sensor (0,01 °C resolution and accuracy of 0,2 °C)
	Motion detection	Precision monitoring XYZ + shock 0,25 -16G
	Light detection	Precise light sensor (0,01 lux till 83000 lux)
0	Alarm	Alarm activates GPS position and event in app
	Event notifications	Event thresholds can be defined and used for event management (o.a. battery status,temperature, humidity)
	Flash	2 MB
	LED's	RGB LED for activity status
9 6	Size	69x39x22mm
a a	Casing	IP68 (waterproof)
	Weight	40 grams
	Battery	½ AA (user replaceable), input 2,2V to 5,5V
	Battery life	Up to 10 years
	Antenna	-5.5 dB in all directions
	Communication	LWAN version 1.0.2, WIFI, BLE
ol lo	Operating temperature	-30°C to +70°C (normal)